












Equipment	Interior Dimensions	Door Opening	Top Opening	Tare Weight	Cubic Capacity	Payload
 <p>20' DRY FREIGHT CONTAINER</p>	L 5,919 mm W 2,340 mm H 2,380 mm	W 2,286 mm H 2,278 mm		1,900 Kg 4,189 lbs	33.0 cbm 1,165 cu.ft	22,100 Kg 48,721 lbs
 <p>40' DRY FREIGHT CONTAINER</p>	L 12,045 mm W 2,309 mm H 2,379 mm	W 2,280 mm H 2,278 mm		3,084 Kg 6,799 lbs	67.3 cbm 2,377 cu.ft	27,396 Kg 60,397 lbs
 <p>40' HIGH CUBE DRY CONTAINER</p>	L 12,056 mm W 2,347 mm H 2,684 mm	W 2,340 mm H 2,585 mm		2,900 Kg 6,393 lbs	76.0 cbm 2,684 cu.ft	29,600 Kg 65,256 lbs
 <p>20' REEFER CONTAINER</p>	L 5,428 mm W 2,226 mm H 2,240 mm	W 2,286 mm H 2,188 mm		2,940 Kg 6,482 lbs	27.5 cbm 971 cu.ft	24,060 Kg 53,043 lbs
 <p>40' REEFER CONTAINER</p>	L 11,207 mm W 2,246 mm H 2,183 mm	W 2,216 mm H 2,118 mm		4,840 Kg 10,670 lbs	54.9 cbm 1,939 cu.ft	25,640 Kg 56,526 lbs
 <p>40' HIGH CUBE REEFER CONTAINER</p>	L 11,628 mm W 2,294 mm H 2,509 mm	W 2,290 mm H 2,535 mm		4,430 Kg 9,766 lbs	66.9 cbm 2,363 cu.ft	28,070 Kg 61,883 lbs
 <p>20' OPEN TOP CONTAINER</p>	L 5,919 mm W 2,340 mm H 2,286 mm	W 2,286 mm H 2,251 mm	L 5,425 mm W 2,222 mm	2,174 Kg 4,793 lbs	31.6 cbm 1,116 cu.ft	21,826 Kg 48,117 lbs
 <p>40' OPEN TOP CONTAINER</p>	L 12,043 mm W 2,340 mm H 2,272 mm	W 2,279 mm H 2,278 mm	L 11,585 mm W 2,162 mm	4,300 Kg 9,480 lbs	64.0 cbm 2,260 cu.ft	26,181 Kg 57,720 lbs
 <p>20' FLAT RACK CONTAINER</p>	L 5,662 mm W 2,438 mm H 2,327 mm			2,530 Kg 5,578 lbs		21,470 Kg 47,333 lbs
 <p>20' COLLAPSIBLE FLAT RACK CONTAINER</p>	L 5,946 mm W 2,126 mm H 2,233 mm			2,900 Kg 6,393 lbs		27,100 Kg 59,745 lbs
 <p>40' FLAT RACK CONTAINER</p>	L 12,080 mm W 2,438 mm H 2,103 mm			5,480 Kg 12,081 lbs		25,000 Kg 55,115 lbs